

UNIVERSAL POWER SUPPLY, 24W



TECHNICAL DATA

GENERAL

Input voltage	100 - 240 VAC
Input frequency	50 / 60 Hz
Input current	0.8 A
Output voltage	24 VDC
Output current	1.0 A
Output connector	4-pin, 3 mm pitch
Input connector	Exchangeable. EU (Type C), UK (Type G), US (Type A), AU (Type I)
Weight	141 g

ADDITIONAL

Input voltage absolute maximum	90 - 264 VAC
Input frequency absolute maximum	47 - 63 Hz
Inrush current	60 A
Output voltage absolute maximum	22.8 - 25.2 VDC
Short circuit protection	✓
HIPOT (dielectric withstand test)	3000 VAC
MTBF	30000 h

Safety: IEC 62368-1:2014+A11:2017
UL 62368-1:2014 Ed.2
CSA C22.2 No. 62368-1:2014 Ed.2
AS/NZS 62368.1:2018

Energy efficiency: EN 50563:2011+A1:2013
EN 50564:2011
10 CFR 430 Appendix Z: 2015

Certification

EMC: EN 55032:2015, Class B
EN 61000-3-2:2014
EN 61000-3-3:2013
EN 55024:2010
FCC Part 15B
AS/NZS CISPR32:2015

